



## Superior Quality 2.4G Wireless Conference System

Succinct designs, pluggable gooseneck microphone with light ring, convenient packing and shipping, the standard aviation 4P head with Lock tight joint, stable and reliable.

This system adopt the most public 2.4G band in the world, the installation without any application, the advanced 2.4G frequency hopping and digital transmission technology, which greatly reduces the variety of interference signals on the system operation. 2.4G has a unique transmission characteristic, Difficult to bypass the big obstacles, the signal hardly to be out of conference room, digital transmission technology, the consummate communication protocol, maximum guarantee of meeting security. System that can meet the needs of ordinary fixed conference room, and can also set up a mobile conference room, and in the convenient premise, providing a highly reliable conferencing solution. Microphone may use two common 1.5V AA batteries, and also support the 1.2V NI-MH battery, standby time up to 20 hours, And continuous speech 7 hours.



EMC02 Chairman Unit  
EMD02 Delegate Unit

### Features:

- Digital encryption self-adaption frequency hopping spread spectrum technology, high confidentiality.
- 24-bit PCM high precision audio signal quantification processing, lossless wireless transmission, the sound quality comparable to wired.
- Built-in frequency shift, feedback suppression, intelligent balancing, etc anti-howling functions, effectively enhance the sound transmission gain.
- Pluggable gooseneck microphone with light ring.
- High sensitivity, effective pick-up range up to 50CM.
- Speech by red lights instructions.
- Support 255 pcs microphone include chairman unit / delegate unit.
- Supports up to 4 microphone Units speaking at the same time.
- Chairman Unit can override all the active delegate units and approve or reject delegates who request to speak. When Chairman Microphone is turned on, the representative microphone can't turn on until Chairman Microphone is off, support 3 Chairman microphone units.
- Microphone may use two common 1.5V AA batteries and support the NI-MH battery, standby time up to 20 hours, And continuous speech 7 hours.

### Additional Operating Accessory:



EMMU02 Main Unit  
Power consumption: Standard: <50 W  
Frequency response: 80-18000 Hz (3 DB)



EM36 Directive Antenna  
Transmission range: 30m (Directional), connect to the main unit directly, Extend line up to 20M.



EM48 Charger Case  
Charging for 12 microphones one time  
Unit power: 1.3W

**EIKI**  
Projectors... and more!  
www.eiki.com

### Eiki International, Inc.

30251 Esperanza ▼ Rancho Santa Margarita, CA 92688-2130  
Phone: 800-242-3454 ▼ Fax: 800-457-3454 ▼ E-mail: usa@eiki.com

In Canada: 9170 County Rd. 93, Ste. 305, P.O. Box 156 ▼ Midland, ON L4R 4K8  
Phone: 800-563-3454 ▼ E-mail: canada@eiki.com